

Company	Model	Display Type	Notes
Format: Model (WEM-MX) - Voltage Inputs - Display Options - Reporting Options - I/O Options - CT Options - Firmware Options			
Energy Tracking. LLC	WEM-MX-120-ND	Voltage 120 VAC. No Display.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%.
Energy Tracking. LLC	WEM-MX-240-ND	Voltage 240 VAC. No Display.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%.
Energy Tracking. LLC	WEM-MX-480-ND	Voltage 480 VAC. No Display.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%.
Energy Tracking. LLC	WEM-MX-120-D	4X20 Line LCD w/o Back light.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%.
Energy Tracking. LLC	WEM-MX-240-D	4X20 Line LCD w/o Back light.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%.
Energy Tracking. LLC	WEM-MX-480-D	4X20 Line LCD w/o Back light.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%.
Energy Tracking. LLC	WEM-MX-120-DBL	4X20 Line LCD with Backlight.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%.
Energy Tracking. LLC	WEM-MX-240-DBL	4X20 Line LCD with Backlight.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%.
Energy Tracking. LLC	WEM-MX-480-DBL	4X20 Line LCD with Backlight.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%.
Energy Tracking. LLC	WEM-MX-XXX-XXX-E	Auto Ranging Voltage from 120 ~ 480 VAC. Display Optional.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%. With Email Reporting .
Energy Tracking. LLC	WEM-MX-XXX-XXX-F	Auto Ranging Voltage from 120 ~ 480 VAC. Display Optional.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%. With FTP Reporting .
Energy Tracking. LLC	WEM-MX-XXX-XXX-EF	Auto Ranging Voltage from 120 ~ 480 VAC. Display Optional.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%. With Email & FTP Reporting .
Energy Tracking. LLC	WEM-MX-XXX-XXX-CB	Auto Ranging Voltage from 120 ~ 480 VAC. Display Optional.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%. With LAN Access to Load Profile data .
Energy Tracking. LLC	WEM-MX-XXX-XXX-EFC	Auto Ranging Voltage from 120 ~ 480 VAC. Display Optional.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%. With Email, FTP & LAN Reporting .
Energy Tracking. LLC	WEM-MX-XXX-XXX-XXX-LC	Auto Ranging Voltage from 120 ~ 480 VAC. Display Optional.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%. Load Control Output options.
Energy Tracking. LLC	WEM-MX-XXX-XXX-XXX-PO	Auto Ranging Voltage from 120 ~ 480 VAC. Display Optional.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%. Pulse Output options.
Energy Tracking. LLC	WEM-MX-XXX-XXX-XXX-XX-SCXXXX:5	Auto Ranging Voltage from 120 ~ 480 VAC. Display Optional.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%. Current Transformers: 5 Amp secondary. Solid Core CTs. CT Primary Amps Rating from 50 Amps to 4000 Amps.

Energy Tracking. LLC	WEM-MX-XXX-XXX-XXX-XX-SPXXXX:5	Auto Ranging Voltage from 120 ~ 480 VAC. Display Optional.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%. Current Transformers: 5 Amp secondary. Split Core CTs. CT Primary Amps Rating from 50 Amps to 6000 Amps.
Energy Tracking. LLC	WEM-MX-XXX-XXX-XXX-XX-SCXXXX:333	Auto Ranging Voltage from 120 ~ 480 VAC. Display Optional.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%. Current Transformers: 333mVAC secondary. Solid Core CTs. CT Primary Amps Rating from 5 Amps to 400 Amps.
Energy Tracking. LLC	WEM-MX-XXX-XXX-XXX-XX-SPXXXX:333	Auto Ranging Voltage from 120 ~ 480 VAC. Display Optional.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%. Current Transformers: 333mVAC secondary. Split Core CTs. CT Primary Amps Rating from 5 Amps to 3000 Amps.
Energy Tracking. LLC	WEM-MX-XXX-XXX-XXX-XX-SPXXXX:333-R	Auto Ranging Voltage from 120 ~ 480 VAC. Display Optional.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%. Current Transformers: 333mVAC secondary. Split Core CTs. CT Primary Amps Rating from 500 Amps to 5000 Amps. The -R is for Rogowski Coil CTs.
Energy Tracking. LLC	WEM-MX-XXX-XXX-XXX-XX-XXXXXX:XXX-X-XX	Auto Ranging Voltage from 120 ~ 480 VAC. Display Optional.	Meets Performance Based Incentive Prog. eligibility with certificate documenting accuracy to less than 2%. Firmware options.
Format: Model (WEM-MX) - Voltage Inputs - Display Options - Reporting Options - I/O Options - CT Options - Firmware Options			